# Detroit Surface care – Acam B.V. Revision nr. 1 Dated 05/06/2019 First compilation Printed on 05/07/2019 Page n. 1/14

# **Safety Data Sheet**

# SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 10708

Product name APC Super Conc

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Not available

1.3. Details of the supplier of the safety data sheet

Name ACAM B.V.
Full address District and Country 5482VR Schijndel
NL

..\_

Tel. (+31) 857 325 754

e-mail address of the competent person

responsible for the Safety Data Sheet fvboxmeer@puriseurope.eu

1.4. Emergency telephone number

For urgent inquiries refer to Tel. (+31) 857 325 754

# **SECTION 2. Hazards identification**

# 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Skin corrosion, category 1 H314 Causes severe skin burns and eye damage.

Serious eye damage, category 1 H318 Causes serious eye damage.

# 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

**APC Super Conc** 

Revision nr. 1

Dated 05/06/2019

First compilation

Printed on 05/07/2019

Page n. 2/14



Signal words: Danger

Hazard statements:

H314 Causes severe skin burns and eye damage.

Precautionary statements:

**P260** Do not breathe dust / fume / gas / mist / vapours / spray.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P280 Wear protective gloves/ protective clothing / eye protection / face protection.
P310 Immediately call a POISON CENTER / doctor / . . .

P264 Wash . . . thoroughly after handling.

Contains: SODIUM METASILICATE

SODIUM HYDROXIDE

# 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

# **SECTION 3. Composition/information on ingredients**

### 3.2. Mixtures

Contains:

2 H319,
2 H319,

# Detroit Surface care – Acam B.V. Revision nr. 1 Dated 05/06/2019 First compilation Printed on 05/07/2019 Page n. 3/14

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## **SECTION 4. First aid measures**

## 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

# **SECTION 5. Firefighting measures**

# 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

# 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

# 5.3. Advice for firefighters

### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## **SECTION 6. Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

# Revision nr. 1 Detroit Surface care - Acam B.V. Dated 05/06/2019 First compilation Printed on 05/07/2019 **APC Super Conc** Page n. 4/14

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

# **SECTION 7. Handling and storage**

### 7.1. Precautions for safe handling

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

# 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s)

Information not available

# **SECTION 8. Exposure controls/personal protection**

# 8.1. Control parameters

# Regulatory References:

DEU	Deutschland	TRGS 900 (Fassung 31.1.2018 ber.) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
DNK	Danmark	Graensevaerdier per stoffer og materialer
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2017
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81

Databank of the social and Economic Concil of Netherlands (SER) Values, AF 2011:18 Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive NI D Nederland EU OEL EU

2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.

**TLV-ACGIH ACGIH 2018** 

2-BUTOXYETHANOL						
Threshold Limit Value	)					
Туре	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	

**APC Super Conc** 

Revision nr. 1

Dated 05/06/2019

First compilation

Printed on 05/07/2019

Page n. 5/14

AGW	DEU	49	10	196	40	SKIN	
MAK	DEU	49	10	98	20	SKIN	
TLV	DNK	98	20			SKIN	
VLA	ESP	98	20	245	50	SKIN	
VLEP	FRA	49	10	246	50	SKIN	
WEL	GBR	123	25	246	50	SKIN	
VLEP	ITA	98	20	246	50	SKIN	
OEL	NLD	100		246		SKIN	
OEL	EU	98	20	246	50	SKIN	
TLV-ACGIH		97	20				

SODIUM HYDROXIDE						
Threshold Limit Value						
Туре	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
TLV	DNK	2				
VLA	ESP	2				
VLEP	FRA	2				
WEL	GBR			2		
TLV-ACGIH				2 (C)		

Legend:

(C) = CEILING : INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

# 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

# HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

### SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

# EYE PROTECTION

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose

# Detroit Surface care – Acam B.V. Revision nr. 1 Dated 05/06/2019 First compilation APC Super Conc Printed on 05/07/2019 Page n. 6/14

class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

### **ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

# **SECTION 9. Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Appearance liquid Colour green Odour characteristic Odour threshold Not available 14 рΗ Melting point / freezing point Not available Initial boiling point Not available Not available Boiling range Flash point Not available **Evaporation Rate** Not available Flammability of solids and gases Not available Lower inflammability limit Not available Upper inflammability limit Not available Lower explosive limit Not available Not available Upper explosive limit 23 mmHa Vapour pressure Not available Vapour density Relative density Not available soluble Solubility

Partition coefficient: n-octanol/water Not available
Auto-ignition temperature Not available
Decomposition temperature Not available
Viscosity Not available
Explosive properties Not available
Oxidising properties Not available

# 9.2. Other information

VOC (Directive 2010/75/EC) : 3,00 % VOC (volatile carbon) : 1,83 %

### Revision nr. 1 Detroit Surface care - Acam B.V. Dated 05/06/2019 First compilation Printed on 05/07/2019 **APC Super Conc**

Page n. 7/14

# **SECTION 10. Stability and reactivity**

## 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

2-BUTOXYETHANOL

Decomposes under the effect of heat.

SODIUM METASILICATE

The aqueous solutions act as: strong bases.Corrodes: aluminium,zinc,tin,aluminium alloys,zinc alloys,tin alloys.

### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

# 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

2-BUTOXYETHANOL

May react dangerously with: aluminium,oxidising agents. Forms peroxides with: air.

SODIUM METASILICATE

Reacts violently with: acids.

# 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

2-BUTOXYETHANOL

Avoid exposure to: sources of heat,naked flames.

SODIUM HYDROXIDE

Avoid exposure to: air,moisture,sources of heat.

# 10.5. Incompatible materials

SODIUM HYDROXIDE

# Revision nr. 1 Detroit Surface care - Acam B.V. Dated 05/06/2019 First compilation Printed on 05/07/2019 **APC** Super Conc Page n. 8/14

Incompatible with: strong acids,ammonia,zinc,lead,aluminium,water,flammable liquids.

## 10.6. Hazardous decomposition products

2-BUTOXYETHANOL

May develop: hydrogen.

# **SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

# 11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

# **ACUTE TOXICITY**

LC50 (Inhalation) of the mixture:

> 20 mg/l LD50 (Oral) of the mixture:

>2000 mg/kg

LD50 (Dermal) of the mixture:

>2000 mg/kg

SODIUM HYDROXIDE

LD50 (Oral) 1350 mg/kg Rat

LD50 (Dermal) 1350 mg/kg Rat

APC Super Conc

Revision nr. 1

Dated 05/06/2019

First compilation

Printed on 05/07/2019

Page n. 9/14

## 2-BUTOXYETHANOL

LD50 (Oral) 615 mg/kg Rat

LD50 (Dermal) 405 mg/kg Rabbit

LC50 (Inhalation) 2,2 mg/l/4h Rat

## SKIN CORROSION / IRRITATION

Corrosive for the skin

Classification according to the experimental Ph value

## SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

# RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

## GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

# CARCINOGENICITY

Does not meet the classification criteria for this hazard class

# REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

# STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

# STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

# ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

# **SECTION 12. Ecological information**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

APC Super Conc

Revision nr. 1

Dated 05/06/2019

First compilation

Printed on 05/07/2019

Page n. 10/14

# 12.1. Toxicity

Information not available

# 12.2. Persistence and degradability

SODIUM HYDROXIDE

Solubility in water > 10000 mg/l

Degradability: information not available

2-BUTOXYETHANOL

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

### 12.3. Bioaccumulative potential

2-BUTOXYETHANOL

Partition coefficient: n-octanol/water 0.81

12.4. Mobility in soil

Information not available

# 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

### 12.6. Other adverse effects

Information not available

# **SECTION 13. Disposal considerations**

### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING
Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

# **SECTION 14. Transport information**

Detroit Surface care – Acam B.V.	Revision nr. 1
Detroit Surface care - Acam B.V.	Dated 05/06/2019
	First compilation
APC Super Conc	Printed on 05/07/2019
7.11 o dapor dono	
	Page n. 11/14
The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods b International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) reg	y Road (ADR) and by Rail (RID), of the gulations.
14.1. UN number	
Not applicable	
14.2. UN proper shipping name	
Not applicable	
14.3. Transport hazard class(es)	
Not applicable	
14.4. Packing group	
Not applicable	
14.5. Environmental hazards	
Not applicable	
14.6. Special precautions for user	
Not applicable	
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code	
Information not relevant	
SECTION 15. Regulatory information	
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture	
Seveso Category - Directive 2012/18/EC: None	

**APC Super Conc** 

Revision nr. 1

Dated 05/06/2019

First compilation

Printed on 05/07/2019

Page n. 12/14

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

3

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

## 15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

# **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Met. Corr. 1 Substance or mixture corrosive to metals, category 1

Acute Tox. 4 Acute toxicity, category 4

Skin Corr. 1A Skin corrosion, category 1A

Skin Corr. 1B Skin corrosion, category 1B

Skin Corr. 1 Skin corrosion, category 1

Eye Dam. 1 Serious eye damage, category 1

Eye Irrit. 2 Eye irritation, category 2
Skin Irrit. 2 Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

H290 May be corrosive to metals.
H302 Harmful if swallowed

**APC Super Conc** 

Revision nr. 1

Dated 05/06/2019

First compilation

Printed on 05/07/2019

Page n. 13/14

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage. H319 Causes serious eve irritation. H315 Causes skin irritation.

H335 May cause respiratory irritation.

### I EGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

## GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament 10. Regulation (EÚ) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP) 13. Regulation (EU) 2017/776 (X Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website

	Povision pr. 1
Detroit Surface care – Acam B.V.	Revision nr. 1
	Dated 05/06/2019
	First compilation
APC Super Conc	Printed on 05/07/2019
·	
	Page n. 14/14
- ECHA website	
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy	
Note for users: The information contained in the present sheet are based on our own knowledge on the date of the last version.	Users must verify the suitability and
thoroughness of provided information according to each specific use of the product.	See a mast verify the suitability and
This document must not be regarded as a guarantee on any specific product property.	
The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, com laws and regulations. The producer is relieved from any liability arising from improper uses.	iply with the current health and salety
Provide appointed staff with adequate training on how to use chemical products.	