# MARINE CERAMIC



## TECHNICAL DATA SHEET





#### **DESCRIPTION:**

PRO MARINE CERAMIC is a transparent, ceramic coating that protects your Car, boat or RV from the harshest of all elements with incredible durability. 2-3 microns in film thickness lasting up to 7 years leaving a super high permanent gloss. PRO MARINE is super concentrated with active ingredients, up to 3 x more than our entry level ceramic coating, super repellent to salt water and a solvent level designed for the marine industry

#### **DIRECTIONS OF USE:**

Shake well and pour several drops to applicator. Apply in a dust free, shaded 6' x 6' sq. ft. area using a lineal strokes with a 10% overlap. Allow the coating to cure for 5 minutes in temps under 90 degrees F, 2-3 minutes over 90 degrees F, you will notice the 'rainbow curing effect'. Wipe down gently frequently flipping your clean dry microfiber towel. Do NOT allow coating to become wet 24 hours after applying. Additional coats can be applied with 1 hour between coats. Always apply in a dust free environment and on a cool, shaded surface.

#### **HEALTH & SAFETY**

Can cause eye irritation. Excessive inhalation may cause respiratory irritation. Ingestion can cause gastrointestinal irritation. Prolonged skin contact may cause slight irritation. Harmful if swallowed. Eyes: Flush with water for 15 minutes, call physician if irritation persists. Inhalation: Remove to fresh air, call physician if irritation persists. Ingestion: Do not induce vomiting, call physician.

### TECHNICAL DATA:

• Flash Point: 120°F (49°C)

Appearance: Clear, Colorless

Physical State: Liquid

Odor: Characteristic

• Specific Gravity: 0.95 g/cm³, 7.92 lbs/US Gal @ 25 C

Dangerous Goods: UN 1993 Flammable Liquid, PG III











5-35°C 41-95°F HS Paint UHS (SRC) Paint