

# CERAMIC COATING

PRO 9H SERIES

## TECHNICAL DATA SHEET



REFERENCE: #50000  
#50002

Sizes:



7 YEARS 6 YEARS 5 YEARS 4 YEARS 3 YEARS 2 YEARS 1 YEAR

DURABILITY SCALE

HIGH LOW

GLOSS SCALE

### TECHNICAL DATA:

- Flash Point 108-113 F (42 - 45 C)
- Appearance: Clear, Colorless
- Physical State: Liquid
- Odor: Characteristic
- Specific Gravity: 0.94 g/cm<sup>3</sup>, 7.92 lb/US Gal @ 25 C

### DESCRIPTION:

5 year protection PRO CERAMIC 9H - is a clear, nano crystalline coating that protects your vehicle from weather, chemicals, and UV rays while repelling water, dirt and other contaminants. CERAMIC COATING 9H applies an ultra hard, durable coating that is 2-3 micron thick and leaves a deep, reflective gloss. Prolong life by maintaining with Re Guard, SiO<sub>2</sub> or Ceramic Spray coating.

### DIRECTIONS OF USE:

Shake well and pour several drops to applicator. Apply in a dust free, shaded 3 x 3 sq. ft. area using a lineal strokes with a 10% overlap. Allow the coating to cure for 5 minutes in temps under 90 degrees F, 2-3 minutes over 90 degrees F, you will notice the 'rainbow curing effect'. Wipe down gently frequently flipping your clean dry microfiber towel. Do NOT allow coating to become wet 24 hours after applying. Additional coats can be applied with 1 hour between coats. Always apply in a dust free environment and on a cool, shaded surface.

### HEALTH & SAFETY

Can cause eye irritation. Excessive inhalation may cause respiratory irritation. Ingestion can cause gastrointestinal irritation. Prolonged skin contact may cause slight irritation. Harmful if swallowed. Eyes: Flush with water for 15 minutes, call physician if irritation persists. Inhalation: Remove to fresh air, call physician if irritation persists. Ingestion: Do not induce vomiting, call physician.



5-35°C  
41-95°F

HS  
Paint

UHS  
(SRC)  
Paint