

EURO CUT 2.0

TECHNICAL DATA SHEET



REFERENCE: #12003
#12004

Sizes:



TECHNICAL DATA:

- Flash Point: >200F (>100.0C)
- Appearance: Light Tan/Off-White
- Physical State: Thick Liquid Creme (Paste - Non-Flowing)
- Odor: Pine / Characteristic
- Specific Gravity: 1.26 g/cm³ 10.5 lbs/US Gal (H₂O = 1)
- Dangerous Goods: Not regulated - US DOT, IATA, IMDG

DESCRIPTION:

EURO CUT 2.0 PASTE Compound is a state of the art premium PASTE compound. Ultra fast acting, designed to remove 1200 – 3000 grit sand scratches. This world class engineered chemistry & formulation provides a high gloss, haze-free finish with easy clean-up and very little swirling. Water based meaning no fillers for permanent results. Silicone-free, body shop safe and VOC compliant. Use with a range of applicators from wool to finishing foam for varied applications.

DIRECTIONS OF USE:

Apply EURO CUT Paste Compound Plus to a 3 ft. by 3 ft. cool surface area. Machine using appropriate 1200 to 1800 rpm and pressure. Gently polish the surface using a 10% overlapping pattern. Keep the applicator flat to the surface. Use a wool or aggressive foam pad for maximum cut. Wipe off residue with microfiber or soft towel.



1. Inspect surface. For removal of 1200 - 3000 grit sand scratches.



2. Attach clean, wool or foam pad, to the D.A. or Rotary machine.



3. Shake before use.



4. Apply to applicator and spread before starting machine.



5. Speed 1200 - 1800 rpm. For a DA mid to high speed and polish until the compounds almost disappears.



6. Polish until almost removed. Use clean microfiber to remove excess.

HEALTH & SAFETY

Can cause eye irritation. Excessive inhalation may cause respiratory irritation. Ingestion can cause gastrointestinal irritation. Prolonged skin contact may cause slight irritation. Eyes: Flush with water for 15 minutes, call physician if irritation persists. Inhalation: Remove to fresh air, call physician if irritation persists. Ingestion: Do not induce vomiting, call physician.

