

PRO CUT

TECHNICAL DATA SHEET



REFERENCE: #14003
#14004

Sizes:



CUT SCALE



GLOSS SCALE

TECHNICAL DATA:

- Flash Point: >200F (>93.3C)
- Appearance: Tan/Light Brown
- Physical State: Thick pourable cream
- Odor: Characteristic
- Specific Gravity: 1.12 g/cm³ 9.35 lbs/US Gal (H₂O = 1)
- Dangerous Goods: Not regulated - US DOT, IATA, IMDG

DESCRIPTION:

PRO CUT Paste Compound is an abrasive compound cleaner that removes 1200-1500 grit sand scratches, oxidation, and water spots with any wool pad. PRO CUT is quick cutting and fast acting, used with very little surface swirling for all types of painted substrates. Easy clean-up. Silicone free, body shop safe and VOC compliant. Follow up with Pro Finish or Swirl X for optimum gloss levels.

DIRECTIONS OF USE:

Apply on an area 3' x 3' in the shade to a 3 ft. by 3 ft. on a cool surface. Machine using appropriate 1200 to 1800 rpm and pressure. Gently polish the surface using a 10% overlapping pattern. Keep the applicator flat to the surface. Use a wool or aggressive foam pad for maximum cut. Wipe off residue with microfiber or soft towel.



1. Inspect surface. For removal of 1200 - 3000 grit sand scratches.



2. Attach clean, wool or foam pad, to the D.A. or Rotary machine.



3. Shake before use.



4. Apply to applicator and spread before starting machine.



5. Speed 1200 - 1800 rpm. For a DA mid to high speed and polish until the compounds almost disappears.



6. Polish until almost removed. Use clean microfiber to remove excess.

HEALTH & SAFETY

Can cause eye irritation. Excessive inhalation may cause respiratory irritation. Ingestion can cause gastrointestinal irritation. Prolonged skin contact may cause slight irritation. Eyes: Flush with water for 15 minutes, call physician if irritation persists. Inhalation: Remove to fresh air, call physician if irritation persists. Ingestion: Do not induce vomiting, call physician.

