

SiO2 PROTECTION

TECHNICAL DATA SHEET



REFERENCE: #26002
#26004

Sizes:



DURABILITY SCALE



GLOSS SCALE

DESCRIPTION:

SiO2 PROTECTION SPRAY is a spray sealant that incorporates the durability and hardness of glass in an easy to apply spray and wipe formula. More than a spray wax, SiO2 PROTECTION SPRAY is made with ceramic silica technology that leaves a surface glassy and smooth. Easy to use on all surfaces SiO2 PROTECTION SPRAY leaves paint, chrome, plastic and glass extremely hydrophobic for 9 months.

DIRECTIONS OF USE:

Shake well. Surface should be clean, shaded and free of solvents or wax before applying SiO2 PROTECTION SPRAY. Product may be applied on top of other ceramic coating every 6 to 9 months. Apply the product after washing, when vehicle surface is clean, dry and cool; do not work in direct sunlight. Wipe off with a clean, dry microfiber towel continually flipping the towel for a non-haze brilliant gloss.



1. Shake well before use.



2. Spray on surface.



3. Use correct applicator to wipe off or to buff.

TECHNICAL DATA:

- Flash Point: Not Determined
- Appearance: White
- Physical State: Liquid
- Odor: Characteristic
- Specific Gravity: .9996 g/cm³, 8.34 lb/US Gal (H2O = 1)
- Dangerous Goods: Not regulated - US DOT, IATA, IMDG

HEALTH & SAFETY

Can cause eye irritation. Excessive inhalation may cause respiratory irritation. Ingestion can cause gastrointestinal irritation. Prolonged skin contact may cause slight irritation. Eyes: Flush with water for 15 minutes, call physician if irritation persists. Inhalation: Remove to fresh air, call physician if irritation persists. Ingestion: Do not induce vomiting, call physician.

