

SLIP AWAY

TECHNICAL DATA SHEET




REFERENCE: #25002
#25004

Sizes:



12 MONTHS 10 MONTHS 8 MONTHS 6 MONTHS 4 MONTHS 2 MONTHS

DURABILITY SCALE



GLOSS SCALE

TECHNICAL DATA:

- Flash Point: Non-Flammable; Will Not Flash (Closed Cup)
- Appearance: Coral
- Physical State: Opaque, Liquid
- Odor: Fruity
- Density: 8.337 lbs/gal
- pH: 5 - 6 (@25°C)
- Specific Gravity: 1.00 g/cm³
- Dangerous Goods: Not regulated - US DOT, IATA, IMDG

DESCRIPTION:


SLIP AWAY is unique, micro-Silica & synthetic polymers and bonding agents combined to deliver a super slick / hydrophobic surface. Perfect and harmless for paintwork, glass, plastic, and rubber. The surface will remain resistant, to detergents, for a detail spray unseen in the industry prior. Effortlessly to apply Can be applied over existing sealants, waxes and ceramic coatings to increase their hydrophobic effect and slip feel. The gloss level must be seen to be believed!

DIRECTIONS OF USE:

Shake well before use. Spray on a cool, shaded surface. Spray product into microfiber towel or directly onto exterior automotive surfaces. Flip towel and polish to a high gloss. Product can be applied to a wet or dry. Can be used in a spray cannon. Flip your towel and wipe dry.



1. Shake well before use.



2. Spray on surface.



3. Use correct applicator to wipe off or to buff.

HEALTH & SAFETY

Can cause eye irritation. Excessive inhalation may cause respiratory irritation. Ingestion can cause gastrointestinal irritation. Prolonged skin contact may cause slight irritation. Eyes: Flush with water for 15 minutes, call physician if irritation persists. Inhalation: Remove to fresh air, call physician if irritation persists. Ingestion: Do not induce vomiting, call physician.

