# PRO FINISH TECHNICAL DATA SHEET

**REFERENCE:** #17003

32 oz

Sizes:

COARSE H

CUT SCALE

**GLOSS SCALE** 

HIGH

#17004

1 Gallon

LOW



#### **DESCRIPTION:**

PRO FINISH POLISH is a light compound & Polish combined that is custom designed to remove imperfections, such a medium swirls, oxidation, minor scratches, etc fast and with ease. Use PRO FINISH POLISH to achieve an ultra-mirror-like flawless finish. Body shop safe and VOC compliant.

### **DIRECTIONS OF USE:**

Shake well. Shake well, use in a shaded area. DA or rotary M/C Use: Use a blended wool pad for heavy imperfections and foam pad for medium imperfections & finishing. Apply evenly to a cool clean 3 ft by 3 ft area. Begin polishing slowly using light to moderate pressure. Decrease pressure as imperfections disappear. Hand Use: Apply a small amount to area. Using a soft terry cloth towel, rub effected area until desired results are achieved.













### TECHNICAL DATA:

ine in the U

**PRO FINISH** 

REACE CAR

- Flash Point: >200F (>93.3C)
- Appearance: White
- Physical State: Creamy liquid
- Odor: Characteristic
- Specific Gravity: 1.0 g/cm<sup>3</sup> 8.27 lbs/US Gal (H2O = 1)
- Dangerous Goods: Not regulated US DOT, IATA, IMDG

1. Inspect surface. For removal of light scratches & heavy Attach clean, polishing foam **3** d, to machine. 4. Apply evenly to panel or pad at spread before starting

l or pad 5. Speed 1200-1800 stroke action. Clean p prevent build up.

6. Polish until product almost removed. Use clean microfibe to remove excess.

## HEALTH & SAFETY

Can cause eye irritation. Excessive inhalation may cause respiratory irritation. Ingestion can cause gastrointestinal irritation. Prolonged skin contact may cause slight irritation. Eyes: Flush with water for 15 minutes, call physician if irritation persists. Inhalation: Remove to fresh air, call physician if irritation persists. Ingestion: Do not induce vomiting, call physician.

