

SLIP AWAY

TECHNICAL DATA SHEET



SiO2 PAINT SEAL

REFERENCE: #27006

Sizes:



DURABILITY SCALE



GLOSS SCALE

DESCRIPTION:

SLIP AWAY DETAIL SPRAY is unique, micro-Silica & synthetic polymers and bonding agents combined to deliver a super slick / hydrophobic surface. Perfect and effective for paintwork, glass, plastic, rubber or on top of existing ceramics waxes etc. The surface is resistant, to detergents, and natures elements. Effortless to apply mist & wipe increasing any hydrophobic effect. The brilliant outstanding gloss level must be seen to be believed!

DIRECTIONS OF USE:

Shake well before use. Spray on a cool surface. Spray product into microfiber towel or directly onto exterior automotive surfaces. Flip towel and polish to a high gloss. Product can be applied to a wet or dry surface. Flip your towel and wipe dry. Can be used in a spray cannon.



1. Shake well before use.



2. Spray on surface.



3. Use correct applicator to wipe off or to buff.

TECHNICAL DATA:

- Flash Point: Non-Flammable; Will Not Flash (Closed Cup)
- Appearance: Coral
- Physical State: Opaque, Liquid
- Odor: Fruity
- Density: 8.337 lbs/gal
- pH: 5 - 6 (@25°C)
- Specific Gravity: 1.00 g/cm3
- Dangerous Goods: Not regulated - US DOT, IATA, IMDG

HEALTH & SAFETY

Can cause eye irritation. Ingestion can cause gastrointestinal irritation. Eyes: Flush with water for 15 minutes. Inhalation: Remove to fresh air, call physician if irritation persists.



5-35°C
41-95°F