SWIRL-X POLISH TECHNICAL DATA SHEET



TECHNICAL DATA:

• Flash Point: >200F (>93.3C)

Appearance: Tan/Light Brown

Physical State: Thick pourable cream

Odor: Characteristic

• Specific Gravity: 1.05g/cm³, 8.75 lb/US Gal (H2O = 1)

• Dangerous Goods: Not regulated - US DOT, IATA, IMDG



DESCRIPTION:

Swirl-X Polish is a modern, fast acting, polish designed to remove 2000 to 3000 grit or finer sand scratches, oxidation, heavy swirls and light scratches. This superior formulation provides a high gloss, haze-free finish with easy clean-up. Silicone-free, body shop safe and VOC compliant. Water based chemistry, Swirl-X contains no fillers, what you see is what you get permanent removal of the defect and a like new condition restored. Perfect for pre-ceramic coating!

DIRECTIONS OF USE:

Shake well. Apply in a cool shaded area, evenly to a 2 ft by 2 ft area. Apply out of direct sunlight, using a rotary polisher or a Dual Action machine with a lamb's wool, microfiber or foam pad, slowly polish using an overlapping pattern with enough pressure to eliminate surface defects. As the polish material diminishes, finesse the paint surface - progressively using less pressure until a high gloss is achieved. Tip – use a light mist of water to achieve an even higher gloss level.













HEALTH & SAFETY

Can cause eye irritation. Excessive inhalation may cause respiratory irritation. Ingestion can cause gastrointestinal irritation. Prolonged skin contact may cause slight irritation. Eyes: Flush with water for 15 minutes, call physician if irritation persists. Inhalation: Remove to fresh air, call physician if irritation persists. Ingestion: Do not induce vomiting, call physician.

















HS **Paint**

UHS (SRC) Paint